

## PowerHub Series Duo Wallbox



### • Intelligent

Connectivity: Wi-Fi+Bluetooth/4G/LAN  
 Smart mobile App control  
 Scheduled charging  
 OCPP 1.6 Jcon  
 5 Inches Colors LCD Screen

### • Flexible Option

Type 2 / Type 1 charging cable /socket  
 16A/32A adjustable output current  
 Floor stand installation  
 App operation/RFID authentication/Plug & Play  
 Compatible with all EV & PHEV models



### • Secure & Safe

Type A+DC 6mA  
 Relay-sticking protection  
 Ergonomic and user-friendly enclosure design  
 Over temperature protection  
 Over&Residual current detection

### • Simple Operation

Start/Stop charging by RFID card  
 Simple HMI with LED indicators  
 Temper glass front panel  
 Robust enclosure  
 Easy installation



## PRODUCT PARAMETER

Datasheet	Model	BSC-AC1402DB	BSC-AC2202DB	BSC-AC4402DB
<b>Electrical Specification</b>	Power Supply	1P+N+PE	3P+N+PE	3P+N+PE
	Rated Voltage	230VAC	400VAC	400VAC
	Rated Current	32A*2	16A*2	32A*2
	Frequency	50/60Hz	50/60Hz	50/60Hz
	Rated Power	7KW*2	11KW*2	22KW*2
<b>Basic Attributes</b>	Charge Connector	Type 2 socket/cable 5M		
	Enclosure	Galvanized steel		
	Left/Right Panel	Temper glass		
	Installation	Wall-mount/Pole-mount(Optional)		
<b>Interactive Interface</b>	LEDIndicator	Green/Blue/Red		
	RFID Reader	MifareISO/IEC14443 A		
	Start Mode	Plug&Play/RFID card/App		
<b>Communication</b>	Emergency Stop	Yes		
	WiFi&Bluetooth	Optional		
	4G	Optional		
	LAN	Optional		
	RFID ( 2 user cards)	Optional		
	OCPP 1.6j	Optional		
<b>Safety</b>	RCD	Type A / Type A+6mA DC		
	Home load balancing	Optional		
	Energy Meter	MID certified(Optional)		
	Ingress Protection	IP55		
	Impact Protection	IK08		
	Electrical Protection	Over current protection,Residual current protection,Surge protection, Over/Under voltage protection, Over/Under frequency protection.Overtemperature protection		
	Certification	CE / FCC		
	Certification Standard	EN IEC61851-1:2019,IEC 61851-1:2017,IEC 61851-21-2:2018		
	Warranty	2 years		
<b>Working Environment</b>	Work Temperature	-40°C~+65°C		
	Work Humidity	5%~95%		
	Work Altitude	<2000m		
<b>Package</b>	Product Dimension	544*409*145mm(H*W*D)		
	Package Dimension	570*430*170mm(L*W*H)		
	Net Weight	21.6kg(cable) / 16.5kg(socket)		
	Gross Weight	24kg(cable) / 19kg(socket)		
	ExternalPackage	Carton		